

## Technical Information

Page 1 of 1

Part No.: 7100.SRM110

# Surface Resistance Meter SRM 110

(Part No.: 7100.SRM110 )

- Pocket size, lightweight, auto ranging surface resistance meter
- Internal parallel electrode (see picture below)  
EN 61340-4-1 probes can be externally connected.
- Measures automatically with 10V and 100V
- Battery operated



### **Caution:**

Touching the electrodes with energized or static highly charged objects might damage the instrument.

### Technical data:

Test voltage	Range	Standard
10 V	$< 10^3 - 10^5 \Omega$	EN 61340-5-1
100 V	$10^6 - > 10^{12} \Omega$	EN 61340-5-1

### Range:

- $10^3 - 10^{12} \Omega$
- Accuracy  $\pm 10\%$

Low battery warning indicated via flashing (>) LED

**Dimensions:**  
130 x 65 x 31mm



### Back side view



### Supplied with:

- Instrument SRM110
- Carrying bag
- 9V-battery (installed)
- Grounding cord
- User's manual
- Calibration certificate



- ▶ 1 year limited warranty
- ▶ Recommended calibration interval: 2 years

We believe all the information in these pages including technical data to be reliable. However we make no warranties expressed or implied and assume no liability regarding any use of this information.

V0806